

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF A PORTION OF THE

EIGHTH GUIDE MERIDIAN WEST, THROUGH TOWNSHIP 47 NORTH,

BETWEEN RANGES 64 AND 65 WEST,

PORTIONS OF THE SOUTH AND WEST BOUNDARIES,

THE NORTH BOUNDARY

AND

A PORTION OF THE SUBDIVISIONAL LINES,

TOWNSHIP 47 NORTH, RANGE 65 WEST,

OF THE SIXTH PRINCIPAL MERIDIAN,

IN THE STATE OF WYOMING.

EXECUTED BY

RYAN R. LORENZEN

SURVEYING TECHNICIAN

under the supervision of

JAMES D. CLAFLIN

CADASTRAL SURVEYOR

Under Special Instructions dated APRIL 30, 1997, approved MAY 1, 1997, which provided for the surveys included under Group Number 638, and assignment instructions dated MAY 1, 1997.

Survey commenced JULY 2, 1997

Survey completed SEPTEMBER 4, 1997

INDEX DIAGRAM

Township 47 North, Range 65 West

23	22	20	18	17	16	
6	76 5	65 4	55 3	43 2	32 1	7
	76	64	53	43	32	
7	74 8	63 9	51 10	41 11	30 12	5
	73	62	51	41	30	
18	72 17	61 16	50 15	39 14	28 13	4
	71	60	49	38	27	
14 19	70 20	59 21	48 22	36 23	26 24	2
70	69	59	48	36	25	
13 30	68 29	58 28	47 27	35 26	25	
67	66	57	46	34		
12 31	65 32	56 33	45 34	33 35	24 36	
11	10	9	9	7		

T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS

The following field notes are those of the dependent resurvey of a portion of the Eighth Guide Meridian West, through Township 47 North, between Ranges 64 and 65 West, portions of the south and west boundaries, the north boundary and a portion of the subdivisional lines, Township 47 North, Range 65 West, of the Sixth Principal Meridian, Wyoming.

Edward F. Stahle surveyed the Eighth Guide Meridian West, through Township 47 North, between Ranges 64 and 65 West, (east boundary) in 1880. Louis Follman retraced the east boundary in 1881, changing the record. W. J. Boland surveyed the remaining exterior boundaries in 1882. F. W. Weisshaar Jr. retraced the exterior boundaries (changing the record back to original on east boundary) and surveyed the subdivisional lines in 1882. Marvin J. Lytle monumented the southeast township corner in 1932. Russell C. MacDonald dependently resurveyed the south boundary in 1951. Ryan R. Lorenzen, under the supervision of James D. Claflin, monumented the northeast township corner in 1992-93.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group Number 638, Wyoming, dated April 30, 1997.

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with a WILD Model T1000 electronic theodolite, a WILD Model DI1600 electronic distance meter and by chaining methods. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian, determined by hour angle observations of the sun at various points along the lines of survey and carried forward by sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The "DEEP-1" is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ ins. long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS

The geographic position of the corner of sections 1, 2, 35 and 36, on the south boundary of the township, based on NAD 83(1986) and determined by satellite positioning methods, is:

Latitude 44° 00' 18.47" N., Longitude 104° 37' 08.45" W.

The mean magnetic declination is 11½° E.

Dependent Resurvey, Portion of the Eighth Guide Meridian,
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

(Restoring the survey executed by
Edward F. Stahle in 1880)

Beginning at the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a sandstone, 19x6x4 ins., alongside, no mks. visible, with brass cap mkd.

T47N	
R65W	R64W
S 24	S 19
<hr/>	
S 25	S 30
1967	
L.S.450	

This position is accepted as the best available evidence of the original cor. position. Bury the unmkd. stone alongside the iron post.

Cor. is located 7.5 lks. W. of fence extending N. and S.

N. 0° 06' E., bet. secs. 19 and 24.

Over gently rolling terrain.

20.115

Point for the S. 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

Dependent Resurvey, Portion of the Eighth Guide Meridian
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

CHAINS	
	<p>T47N R65W R64W S1/16 S 24 S 19 1997</p> <p>Cor. is located 5.6 lks. W. of fence extending N. and S.</p>
40.23	<p>The 1/4 sec. cor. of secs. 19 and 24, at intersection of fences extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p>T47N R65W R64W 1/4 S 24 S 19 1997</p> <p>From this point, a position established by person(s) unknown, bears N. 17° 05' E., 33.4 lks. dist., monumented with a steel reinforcement rod, 3/4 in. diam., firmly set, projecting 5 ins. above the ground, with a broken steel sign post lying alongside. This position is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>N. 0° 21' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
40.29	<p>The cor. of secs. 13, 18, 19 and 24, monumented by Delbert E. Robinson, Wyoming Professional Engineer and Land Surveyor No. 441, with an iron post, 30 ins. long, 1 in. diam., firmly set 19 ins. in the ground, with brass cap mkd. T47N R64W R65W S13 S18 S19 S24 1961 REG. NO. 441. This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Eighth Guide Meridian
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

CHAINS	
	<div data-bbox="852 306 1003 491" data-label="Text"> <p>T47N R65W R64W S 13 S 18 <hr/>S 24 S 19 1997</p> </div> <p>Deposit the 1 in. iron post inside the iron post.</p> <p>Cor. is located 7.3 lks. E. of fence extending N. and S.</p> <hr/> <p>N. 0° 13' E., bet. secs. 13 and 18.</p> <p>Over nearly level terrain.</p>
20.155	<p>The S. 1/16 sec. cor. of secs. 13 and 18, monumented by Delbert E. Robinson, Wyoming Professional Engineer and Land Surveyor No. 441, with an iron post, 30 ins. long, 1 in. diam., firmly set 20 ins. in the ground, with brass cap mkd. S1/16 S13 S18 1961 REG. NO. 441. This position is accepted as a careful and faithful determination of the cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div data-bbox="847 1226 1002 1379" data-label="Text"> <p>T47N R65W R64W S1/16 S 13 S 18 1997</p> </div> <p>Deposit the 1 in. iron post inside the iron post.</p> <p>Cor. is located 4.7 lks. E. of fence extending N. and S.</p> <hr/> <p>N. 0° 13' E., beginning new measurement.</p> <p>Over nearly level terrain.</p>
20.14	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Eighth Guide Meridian
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

CHAINS	
	<p>T47N R65W R64W 1/4 S 13 S 18 1997</p> <p>Cor. is located 8.3 lks. E. of fence extending N. and S.</p>
40.28	<p>Point for the N. 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
	<p>T47N R65W R64W N1/16 S 13 S 18 1997</p> <p>Cor. is located N. 12¾° E., 9.6 lks. dist., from intersection of fences extending N., S. and W.</p>
60.42	<p>The cor. of secs. 7, 12, 13 and 18, monumented by Delbert E. Robinson, Wyoming Professional Engineer and Land Surveyor No. 441, with an iron post, 2½ ins. diam., firmly set, projecting 15 ins. above the ground, at intersection of fences extending N., S., W. with projection of abandoned fence from the E., with brass cap mkd.</p>
	<p>T47N R65W R64W S 12 S 7 — S 13 S 18 1961 REG. NO. 441</p> <p>This position is accepted as the best available evidence of the original cor. position.</p>
	<p>N. 0° 20' E., bet. secs. 7 and 12.</p> <p>Over nearly level terrain, along fence, gradually becoming abandoned.</p>
37.85	<p>Abandoned fence extending SE. and NW., approximately 15 lks. W. of cor. of abandoned fences extending S. and NW.</p>

Dependent Resurvey, Portion of the Eighth Guide Meridian
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

CHAINS	
40.32	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented by Robert L. St. Claire, Wyoming Registered Land Surveyor No. 584, with an aluminum post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">R65W T47N R64W 1/4 S 12 S 7 LS 584 1981</p> <p>This position is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>From this point, a position monumented by person(s) unknown, bears S. 47° 33' E., 1.05 chs. dist., an iron pipe, 1½ ins. diam., firmly set, projecting 4 ins. above the ground, with steel electric fence post set and wooden post lying alongside. This position is not accepted as the best available evidence of the original cor. position.</p> <p>Cor. is located 26.8 lks. W. of projection of abandoned fence from the S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 20' E., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
15.00	Enter timber.
40.03	Center line of N. track of double railroad tracks extending ESE. and WNW. on a curve.
40.32	<p>Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance, area has been disturbed by recent railroad reconstruction; there is no remaining evidence of the monument set by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, as filed in the Weston County Court House, nor of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R65W R64W S 1 S 6 <hr style="width: 50%; margin: 0 auto;"/>S 12 S 7 1997</p>

Dependent Resurvey, Portion of the Eighth Guide Meridian
through T. 47 N., between Rs. 64 and 65 W.,
Sixth Principal Meridian, Wyoming

CHAINS	
	N. 0° 20' E., bet. secs. 1 and 6.
	Over rolling terrain, through timber.
23.30	Wyoming State Highway No. 16, bears SE. and NW.
40.32	The 1/4 sec. cor. of secs. 1 and 6, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, as filed at the Weston County Court House, with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S 1 S 6 1967 L.S. 450 </div>
	This position is accepted as a careful and faithful reestablishment of the original cor. position.
	Cor. is located S. 51° E., 40.2 lks. dist., from cor. of fences extending S. and W., which is 7.5 lks. N. of intersection of fences N., E. and S.
	<hr/>
	N. 0° 16' E., beginning new measurement.
	Over rolling terrain, through timber.
9.00	Leave timber.
40.32	The cor. of Tps. 47 and 48 N., Rs. 64 and 65 W., monumented with an iron post, 2½ ins. diam., as described in the 1992-93 field notes of the dependent resurvey, T. 48 N., R. 64 W.
	<hr/>
	Dependent Resurvey, Portion of the South Boundary, T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming
	<hr/>
	(Restoring the dependent resurvey executed by Russell C. MacDonald in 1951)
	<hr/>
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set flush with the surface of the ground, with a sandstone, 12x10x4 ins., buried alongside, no mks. visible, and a wooden fence post lying alongside, with brass cap mkd.

Dependent Resurvey, Portion of the South Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS

T47N R65W

S 35 | S 36

S 2 | S 1

T46N

1951

Set a steel fence post alongside the iron post.

S. 89° 32' W., bet. secs. 2 and 35.

Over rolling terrain.

40.39

The 1/4 sec. cor. of secs. 2 and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a wooden fence post lying alongside, with brass cap mkd.

S 35

1/4 ———

S 2

1951

Reset wooden fence post alongside the iron post.

S. 89° 32' W., beginning new measurement.

Over rolling terrain.

40.39

Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance by method of irregular bdy. adjustment; recovered the 1951 monument lying loose along W. right-of-way fence of Weston County Road No. 59, gravel extending N. and S.

Reset the 1951 iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T47N R65W

S 34 | S 35

S 3 | S 2

T46N

1951 1997

Set a steel fence post alongside the iron post.

Dependent Resurvey, Portion of the South Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>S. 89° 34' W., bet. secs. 3 and 34.</p> <p>Over rolling terrain.</p> <p>40.33 The 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with a wooden fence post lying alongside, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 34 1/4 ——— S 3 1951</p> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>S. 89° 36' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>40.30 The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with badly weathered sandstone, 13x6x1 ins., alongside, no mks. visible, 1.5 lks. W. of fence extending N. and S., with brass cap mkd.</p> <div style="text-align: center;"> <p>T47N R65W S 33 S 34 ——— S 4 S 3 T46N 1951</p> </div> <p>Bury the unmkd. stone alongside the iron post.</p> <hr/> <p>S. 89° 24' W., bet. secs. 4 and 33.</p> <p>Over rolling terrain.</p> <p>40.52 The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a scattered mound of stone N. of the cor., with brass cap mkd.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the South Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div data-bbox="873 310 1003 436" style="text-align: center;"> <p>S 33 1/4 ——— S 4 1951</p> </div> <p data-bbox="435 468 1430 531">Set a steel fence post alongside the iron post and rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr data-bbox="703 552 1182 562"/> <p data-bbox="435 594 1084 625">S. 89° 24' W., beginning new measurement.</p> <p data-bbox="435 657 764 688">Over rolling terrain.</p>
40.48	<p data-bbox="435 720 1458 846">The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set flush with the surface of the ground, with small embedded mound of stone W. of cor. and a wooden fence post lying alongside, with brass cap mkd.</p> <div data-bbox="865 884 1011 1066" style="text-align: center;"> <p>T47N R65W S 32 S 33 ——— S 5 S 4 T46N 1951</p> </div> <p data-bbox="435 1098 1174 1129">Set a steel fence post alongside the iron post.</p> <hr data-bbox="435 1161 1466 1171"/> <p data-bbox="435 1192 979 1224">S. 89° 02' W., bet. secs. 5 and 32.</p> <p data-bbox="435 1255 760 1287">Over rolling terrain.</p>
40.33	<p data-bbox="435 1329 1450 1455">The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a scattered mound of stone N. of the cor., at cor. of fences extending N., E. and abandoned S., with brass cap mkd.</p> <div data-bbox="865 1493 995 1612" style="text-align: center;"> <p>S 32 1/4 ——— S 5 1951</p> </div> <hr data-bbox="695 1633 1174 1644"/> <p data-bbox="435 1675 1076 1707">S. 88° 59' W., beginning new measurement.</p> <p data-bbox="435 1738 751 1770">Over rolling terrain.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.52	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with a sandstone, 16x12x1 ins., alongside, no mks. visible, 1 lk. W. of fence extending N. and S., with brass cap mkd.</p> <div data-bbox="911 485 1057 667"> <p>T47N R65W S 31 S 32 ----- S 6 S 5 T46N 1951</p> </div> <p>Bury the unmkd. stone alongside the iron post.</p> <hr/> <p>S. 89° 50' W., bet. secs. 6 and 31.</p> <p>Over rolling terrain.</p>
40.38	<p>The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div data-bbox="894 1056 1019 1178"> <p>S 31 1/4 ——— S 6 1951</p> </div> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>S. 89° 23' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
39.09	<p>The cor. of Tps. 46 and 47 N., Rs. 65 and 66 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div data-bbox="873 1560 1019 1780"> <p>T47N R66W R65W S 36 S 31 ----- S 1 S 6 T46N 1951</p> </div> <p>Set a steel fence post alongside the iron post.</p>

Dependent Resurvey, Portion of the South Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p>Cor. is located 53.6 lks. E. of intersection of abandoned fences extending N., S. and W.</p> <hr/> <p>Dependent Resurvey, Portion of the West Boundary, T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming</p> <hr/> <p>(Restoring the survey executed by W. J. Boland in 1882)</p> <hr/> <p>From the cor. of Tps. 46 and 47 N., Rs. 65 and 66 W. N. 0° 32' E., bet. secs. 31 and 36. Over rolling terrain, converging with abandoned fence.</p> <p>40.58 Point for the 1/4 sec. cor. of secs. 31 and 36, determined latitudinally by proportionate measurement and longitudinally by abandoned fence extending N. and S.; there is no remaining evidence of the original monument.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R66W R65W 1/4 S 36 S 31 1997</p> <p>Set a steel fence post alongside the iron post.</p> <hr/> <p>N. 0° 39' E., beginning new measurement. Over rolling terrain, along abandoned fence.</p> <p>20.29 Point for the N. 1/16 sec. cor. of secs. 31 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the West Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
40.58	<p style="text-align: center;">T47N R66W R65W N1/16 S 36 S 31 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 3 lks. E. of abandoned fence extending N. and S.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 14X12X3 ins., firmly set 12 ins. in the ground, upper portion fragmented, no mks. visible, in fence extending N. and S. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T47N R66W R65W S 25 S 30 ----- S 36 S 31 1997</p> <p>Bury the unmkd. stone alongside the iron post.</p> <p>Cor. is located 33 lks. N. of intersection of fences extending N., E. and W.</p>
40.28	<p>N. 1° 09' E., bet. secs. 25 and 30.</p> <p>Over rolling terrain, leaving fence.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with a sandstone, 11X9X2 ins., firmly set 10 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the West Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<div data-bbox="873 310 1029 466"> <p>T47N R66W R65W 1/4 S 25 S 30 1997</p> </div> <div data-bbox="444 499 1438 558"> <p>Bury the unmkd. stone and set a steel fence post alongside the iron post.</p> </div> <div data-bbox="444 592 1318 630"> <p>Cor. is located 90 lks. E. of fence extending N. and S.</p> </div> <hr data-bbox="711 655 1192 663"/> <div data-bbox="444 688 1078 726"> <p>N. 1° 06' E., beginning new measurement.</p> </div> <div data-bbox="444 751 773 789"> <p>Over rolling terrain.</p> </div> <div data-bbox="295 814 1419 970"> <p>40.50 The cor. of secs. 19, 24, 25 and 30, monumented with a sandstone, 18X14X2 ins., firmly set 10 ins. in the ground, no mks. visible, in fence extending E. and W. This position is accepted as the best available evidence of the original cor. position.</p> </div> <div data-bbox="438 1003 743 1041"> <p>At the corner point</p> </div> <div data-bbox="438 1066 1412 1159"> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> </div> <div data-bbox="867 1201 1016 1390"> <p>T47N R66W R65W S 24 S 19 S 25 S 30 1997</p> </div> <div data-bbox="431 1415 1162 1453"> <p>Bury the unmkd. stone alongside the iron post.</p> </div> <hr data-bbox="431 1486 1471 1495"/> <div data-bbox="431 1512 987 1549"> <p>N. 1° 12' E., bet. secs. 19 and 24.</p> </div> <div data-bbox="431 1575 873 1612"> <p>Over gently rolling terrain.</p> </div> <div data-bbox="285 1638 1422 1772"> <p>40.74 The 1/4 sec. cor. of secs. 19 and 24, monumented with a sandstone, 11X11X2 ins., firmly set 8 ins. in the ground, no mks. visible. This position is accepted as the best available evidence of the original cor. position.</p> </div> <div data-bbox="425 1797 730 1835"> <p>At the corner point</p> </div>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CHAINS

T47N
R66W R65W
1/4
S 24 | S 19
1997

N. 1° 34' E., beginning new measurement.

Over gently rolling terrain.

39.80 The cor. of secs. 13, 18, 19 and 24, monumented at record bearing and distance from the witness cor. established by Ralph W. Goodson, Wyoming Professional Engineer and Land Surveyor No. 2395,

An aluminum post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with aluminum cap mkd. T47N R65W T47N R66W 13 18 19 24 W.C. 30 1982 PE&LS 2395, with an arrow pointing toward the cor., as filed at the Weston County Court House, bears NORTH, 45.5 lks. dist.

Reset the aluminum post flush with the surface of the ground.

This position is accepted as the best available evidence of the original cor. position.

At the true point

Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.

T47N	
R66W	R65W
S 13	S 18
<hr/>	
S 24	S 19
1997	

Cor. is located on N. edge of trail road extending E. and W.

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<p>(Restoring the survey executed by W. J. Boland in 1882)</p> <hr/>
	<p>From the cor. of Tps. 47 and 48 N., Rs. 64 and 65 W.</p>
	<p>N. 88° 36' W., bet. secs. 1 and 36.</p>
	<p>Over rolling terrain, gradually leaving dirt road.</p>
37.43	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">1/4 S 36 <hr/>S 1 1967 L.S. 450</p>
	<p>This position was filed at the Weston County Court House and is accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p>Cor. is located 79 lks. N. of dirt road extending E. and W.</p> <hr/>
	<p>N. 88° 36' W., beginning new measurement.</p>
	<p>Over gently rolling terrain.</p>
15.00	<p>Wyoming State Highway No. 116, bears SE. and NW.</p>
37.44	<p>The cor. of secs. 1, 2, 35 and 36, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 30 ins. long, 1 in. diam., firmly set 22 ins. in the ground, with brass cap mkd. 1963 T48N T47N R65W 1 2 35 36 LTP 450, at intersection of fences extending N., S. and W. This position was filed at the Weston County Court House and is accepted as the best available evidence of the original cor. position.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
	<div style="text-align: center;"> T48N R65W S 35 S 36 <hr style="width: 50%; margin: 0 auto;"/> S 2 S 1 T47N 1997 </div> <p>Deposit the 1 in. iron post inside the iron post.</p> <hr/> <p>S. 89° 05' W., bet. secs. 2 and 35.</p> <p>Over nearly level terrain.</p> <p>37.25 Wyoming State Highway No. 116, bears NE. and SW.</p> <p>39.10 Access road, bears NE. and SW.</p> <p>40.32 The 1/4 sec. cor. of secs. 2 and 35, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, in collar of stone, brick and concrete, with an iron pipe, 2 ins. diam., set alongside, broke flush with the surface of the ground, upper portion, 43 ins. long, lying alongside, with brass cap mkd.</p> <div style="text-align: center;"> 1967 1/4 S 35 <hr style="width: 50%; margin: 0 auto;"/> S 2 L.S.450 </div> <p>This position was filed in the Weston County Court House and is accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 89° 02' W., beginning new measurement.</p> <p>Over nearly level terrain.</p> <p>0.60 Intersection of fences extending NE., SW. and W.; thence along fence.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	
20.18	<p>The W. 1/16 sec. cor. of secs. 2 and 35, monumented by Richard T. Doyle, Wyoming Registered Land Surveyor No. 2333, with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground, with yellow plastic cap mkd. RLS 2333, 7.5 lks. S. of fence cor. extending N. and E. This position is accepted as a careful and faithful determination of the cor. position.</p> <hr/> <p>S. 89° 02' W., beginning new measurement.</p> <p>Over gently rolling terrain.</p>
20.18	<p>The cor. of secs. 2, 3, 34 and 35, monumented by Lawrence T. Price, Wyoming Registered Land Surveyor No. 450, with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with a small steel sign post alongside, with brass cap mkd.</p> <div style="text-align: center;"> <p>R65W T48N S 34 S 35 <hr/>S 3 S 2 T47N 1967 L.S.450</p> </div> <p>This position was filed in the Weston County Court House and is accepted as the best available evidence of the original cor. position.</p> <hr/> <p>S. 88° 56' W., bet. secs. 3 and 34.</p> <p>Over gently rolling terrain.</p>
15.00	Mining access road, bears SE. and NW.
25.30	Airstrip, bears SSE. and NNW.
40.25	<p>Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS	<p style="text-align: center;">T48N R65W S 34 1/4 ——— S 3 T47N 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 84° 38' E., 85.6 lks. dist., a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, with unmkd. yellow plastic cap. This position was established using inappropriate methods and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located 9 lks. S. of fence extending irregularly E. and W.</p> <p>60.375 Point for the W. 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T48N R65W S 34 W1/16 ——— S 3 T47N 1997</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 78° 51' E., 68.3 lks. dist., a steel reinforcement rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with unmkd. yellow plastic cap. This position was established using inappropriate methods and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located 14.5 lks. S. of fence extending irregularly E. and W.</p> <p>63.00 Coyote Creek, course SSE.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the North Boundary,
T. 47 N., R. 65 W., Sixth Principal Meridian, Wyoming

CHAINS													
80.50	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T48N</td><td>R65W</td></tr> <tr><td>S 33</td><td>S 34</td></tr> <tr><td colspan="2"><hr/></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td colspan="2">T47N</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by person(s) unknown, bears N. 70° 00' E., 53.2 lks. dist., a steel reinforcement rod, ¾ in. diam., firmly set, projecting 4 ins. above the ground, 2.3 lks. W. of intersection of fences extending N., E. and irregularly W. This position is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <hr/> <p>S. 88° 56' W., bet. secs. 4 and 33.</p> <p>Over rolling terrain.</p>	T48N	R65W	S 33	S 34	<hr/>		S 4	S 3	T47N		1997	
T48N	R65W												
S 33	S 34												
<hr/>													
S 4	S 3												
T47N													
1997													
20.125	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T48N</td><td>R65W</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>E 1/16</td><td>—</td></tr> <tr><td>S 4</td><td></td></tr> <tr><td colspan="2">T47N</td></tr> <tr><td colspan="2">1997</td></tr> </table> </div> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, a position monumented by Theodore J. Vore, Wyoming Professional Engineer No. 1088, bears N. 71° 32' E., 70.1 lks. dist., a steel reinforcement rod, ¾ in. diam., firmly set, projecting 2 ins. above the ground. This position was established using inappropriate methods and is not accepted as a careful and faithful determination of the cor. position.</p>	T48N	R65W	S 33		E 1/16	—	S 4		T47N		1997	
T48N	R65W												
S 33													
E 1/16	—												
S 4													
T47N													
1997													